



Product Service

CERTIFICATE

No. Z1A 090361 0044 Rev. 00

Holder of Certificate: **Kinnarps AB**

Industrigatan 1
521 88 Kinnarp
SWEDEN

Certification Mark:



Product:

Office chairs
Office work chairs

Tested according to:

DIN EN 1335-1:2023
DIN EN 1335-2:2019
PPP 51054D:2023
AfPS GS 2019:01 PAK

With this certificate, in its capacity as a notified GS body, TÜV SÜD Product Service GmbH issues the GS Mark to the named certificate holder for the declared product with the named model designation in accordance with section 20 ProdSG (German Product Safety Act). The product meets the safety and health requirements of section 20 (3) ProdSG. The manufacturer is reminded of their obligations in accordance with section 24 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition, the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 713281751

Valid until: 2029-04-29

Date, 2024-04-30

(Jens Biesenack)

CERTIFICATE

No. Z1A 090361 0044 Rev. 00

Model(s): **Plus [6]**
6770, 6772, 6774, 6780, 6782, 6784

Parameters:

Type Overview	6770: with low backrest and without armrest 6772: with low backrest and 2D armrest 6774: with low backrest and 4D armrest 6780: with high backrest and without armrest 6782: with high backrest and 2D armrest 6784: with high backrest and 4D armrest
Seat	Upholstered, adjustable in height and depth, synchrone mechanism
Seat height adjustment	400 – 535 mm By gas spring S.C. Stabilus Romania S.R.L. Tube type: STAB-O-MAT D; material 0106184, Outside diameter: 28 mm Wall thickness: 2.5 mm; Surface finish: plasma nitrified
Seat depth	425 – 520 mm
Backrest	Upholstered
Headrest	Optional
Backrest height (above seat)	555 mm (6770 / 6772 / 6774) or 605 mm (6780 / 6782 / 6784)
Backrest width	415 mm
Armrest (optional)	Plastic frame and armrest pad, 2D or 4D armrest
Distance between armrests	410 – 520 mm (2D) or 335 – 520 mm (4D)
Armrest height	165 – 290 mm
Armrest length	235 mm (2D) or 254 mm (4D)
Base	Plastic or aluminium
Maximum offset of the underframe	364 mm
Swivel chair type	Type A (according to DIN EN 1335-1:2023)